


STECCO 19401



SE: Rengöring: Torkas med torr trasa.
NO: Rengjøring: Tørkes av med tørr klut.
FI: Puhdistus: Pyyhi kuivalla liinalla.
EN: Cleaning: Wipe with a dry cloth.

NO: Dette produktet inneholder en lyskilde med energieffektivitetsklasse F. Diodelyskilderne kan skiftes som reservdeler av fagman. Levetid 50000 timer ≈ 20 år (6 timer/dag)

SE: Denna produkt innehåller en ljuskälla med energieffektivitetsklass F. Lysdioderna är utbytbara som reservdelar av fackman. Lifstid 50000 tim ≈ 20 år (6 tim/dag)

FI: Tämä tuote sisältää valonlähteen, jonka energiatehokkuusluokka on F. LED valolähde vaihdetta vissa asiantuntijan toimesta. Käyttöikä 50 000 tuntia ≈ 20 vuotta (6 t/päivä)

EN: This product contains a light source of energy efficiency class F. The LED light source is exchangeable by a specialist. Lifetime 50000 h ≈ 20 years (6 h/day)

Light Source :

Lighting technology used: LED
Mains or non-mains: non-mains
Directional or non-directional: non-directional
Connected L.S.: no
Color-tuneable: no
Envelope: no
High luminance: no
Anti-glare shield: no
Dimmable: yes
Energy consumption in on-mode: 13 kWh / 1000 h**
Energy efficiency class (A-G): F
Useful luminous flux: 1400 lm*
CCT colour temperature: 3000 K
On-mode power: 12.2 W**
CRI: ≥ 80
R9 color rendering index: 5
Chromaticity coordinates: x:0.434, y:0.403
SDCM: < 6
Lifetime L₈₀B₅₀: 50 000 hours
Lumen maintenance factor: 0.96
Survival factor: 0.90
Supply current: 24VDC

* The luminous flux stated here is the value for the light source itself in accordance with Regulation (EU) 2019/2015. On the box the luminous flux for the lighting fitting is stated, where the light is partly absorbed by glass/glare shield/shade and parts of the fitting, why it is lower than for the light source.

**Power consumption / power for LED only.
Power consumption including driver is about 15 kWh/1000h on max light.



aneta.se
aneta.no



aneta_lighting

